

GJax gjs:form

From Intranet

Table of contents

1 Level 5

1.1 Synopsis

1.2 Examples

2 Templates

2.1 Notes

Level 5

Synopsis

```
<xsl:import href='gjsForm.xsl' />

<gjs:form
  title='form title'
  jsFile='associated javaScript file'
  save='{ /Form/@save}'
  close='{ /Form/@close}'
  delete='{ /Form/@delete}'
  print='{ /Form/@print}'
  help='{ /Form/@help}'
  ok='{ /Form/@ok}'
  cancel='{ /Form/@cancel}'
  locale='{ /Form/user/@locale}'>

  <gjs:information>
  <gjs:tabStrip>
    <gjs:tabStripTab>
  <gjs:frame>
    <gjs:columnWidths>
      <gjs:column>
    <gjs:fields>
```

```
</gjs:form>
```

Examples

```
<xsl:import href='gjsForm.xsl' />

<xsl:template match="Form">

  <gjs:form
    title='Patient Details'
    jsFile='Patient.js'
    save='{/Form/@save}'
    close='{/Form/@close}'
    delete='{/Form/@delete}'
    print='{/Form/@print}'
    help='{/Form/@help}'
    ok='{/Form/@ok}'
    cancel='{/Form/@cancel}'>

    <gjs:information>
      Details of the patient, associated diagnosis and treatments.
    </gjs:information>

    <gjs:tabStrip>
      <gjs:tabStripTab
        id='tabPatient'
        accesskey='D'
        divId='divPatient'>
        Details
      </gjs:tabStripTab>
      <gjs:tabStripTab
        id='tabDiagnosis'
        accesskey='G'
        divId='divDiagnosis'>
        Diagnosis
      </gjs:tabStripTab>
    </gjs:tabStrip>

    <!-- Patient details frame -->
    <div id='divPatient' class='visible' style='height: 240'>
      <gjs:frame>

        <!-- Set up frame column widths -->
        <gjs:columnWidths>
          <gjs:column width='100px' />
          <gjs:column width='600px' />
        </gjs:columnWidths>

        <!-- Input fields for the patient details frame -->
        <gjs:fields>
          <gjs:input
            id='patient'
            accesskey='P'
            size='20'
            maxlength='40'
            value='{@patient}'
            onchange='Form.fnChanged()'>
            <label><u>P</u>atient</label>
            <hint>Enter the patient identifier</hint>
          </gjs:input>

        </gjs:fields>

      </gjs:frame>
    </div>

    <!-- Diagnosis and treatment Frame -->
    <div id='divDiagnosis' class='visible' style='height: 240'>

      <gjs:frame>

        <!-- Set up frame column widths -->
        <gjs:columnWidths>
          <gjs:column width='100px' />
          <gjs:column width='600px' />
        </gjs:columnWidths>

        <gjs:fields>
          <gjs:input
            id='diagnosis'
            accesskey='D'
            size='20'
            maxlength='40'
            value='{@diagnosisICD10}'
            onchange='Form.fnChanged()'>
            <label><u>D</u>iagnosis</label>
            <hint>Enter the diagnosis ICD-10 code for this patient</hint>
          </gjs:input>


```

Templates

- `<xsl:template name="gjs:buttonBar">` The standard button bar template provides OK/Cancel or Save/Close and Delete, Print and Help buttons. This can be overridden if a custom button-bar is required.
- `<xsl-template name="gjs:buttonBarBefore">` A template of this name will include it's content to the left of the standard button bar. This can be used to add additional buttons to the left of the button bar.
- `<xsl-template name="gjs:buttonBarAfter">` A template of this name will include it's content to the right of the standard button bar. This can be used to add additional buttons to the right of the button bar.

Notes

Generally, the locale property should be supplied at the form level and will then apply to all date controls on the page. It can be overridden on individual `<gjs:inputDate>` elements if you wanted to, say, force a date to be input in US format, but this would be quite unusual.

Retrieved from "http://10.101.68.18/intranet/index.php/GJax_gjs:form"

- This page was last modified 00:08, 24 Jan 2006.