

# GJax gjs:caption

## From Intranet

gJax Developers Guide

### Table of contents

- 1 gjs:caption
  - 1.1 Level 5
    - 1.1.1 Synopsis
    - 1.1.2 Examples
    - 1.1.3 Notes
  - 1.2 Level 4
    - 1.2.1 Synopsis
    - 1.2.2 Examples
    - 1.2.3 Notes

## gjs:caption

A control for displaying a caption on a form. Can be used for a stand alone caption or in conjunction with some other control as a label for that control.

It can be used at level 5 or level 4.

```
<gjs:caption  
    for='gaga'  
    accesskey='X'  
    readonly='0|1'    Default: 0  
>  
    <label>Xyz</label>  
</gjs:caption>
```

## Level 5

### Synopsis

```
<xsl:include href='gjsForm.xsl' />  
  
<gjs:form  
...  
locale='{/Form/user/@locale}'>  
  
<gjs:caption  
    for='gaga'  
    accesskey='X'  
    readonly='0|1'    Default: 0  
>  
    <label>Xyz</label>  
</gjs:caption>
```

### Examples

```
<gjs:caption  
for='customerName'  
accesskey='N'  
readonly='0'>  
  <label>Customer Name</label>  
</gjs:caption>
```

```
<gjs:caption  
readonly='1'>  
  <label>Supplier Name</label>  
</gjs:caption>
```

```
<gjs:caption  
for='patient'  
accesskey='P'>  
  <label>Patient</label>  
</gjs:caption>
```

## Notes

The style of the caption is inherited from the user's desktop settings; the font size, face and colour are all inherited.

The *for* and *accesskey* attributes are used to associate a caption with an input field on the form. They are not required for *read only* captions.

## Level 4

### Synopsis

```
<xsl:include href='gjsControls.xsl' />  
  
<link rel='StyleSheet' href='gjsForm.css' type='text/css' />  
<script src='Calendar.js' />
```

```
<gjs:caption  
for='gaga'  
accesskey='X'  
readonly='0|1'  Default: 0  
>  
  <label>Xyz</label>  
</gjs:caption>
```

### Examples

```
<xsl:include href='gjsControls.xsl' />

<xsl:template match="Form">
  <html>
    <head>
      <link rel='StyleSheet' href='gjsForm.css' type='text/css' />
    </head>
    <body>

      <table>
        <tr>
          <gjs:caption
            for='customerName'
            accesskey='N'
            readonly='0'>
            <label>Customer Name</label>
          </gjs:caption>
        </tr>

        <tr>
          <gjs:caption
            readonly='1'>
            <label>Supplier Name</label>
          </gjs:caption>

          <gjs:caption
            for='patient'
            accesskey='P'>
            <label>Patient</label>
          </gjs:caption>
        </tr>
      </table>
    </body>
  </html>
</xsl:template>
```

## Notes

The style of the caption is inherited from classes *caption* and *captionDisabled*. If gjsForm.css is used then the style is inherited from the user's desktop settings; the font size, face and colour are all inherited.

The *for* and *accesskey* attributes are used to associate a caption with an input field on the form. They are not required for *read only* captions.

Retrieved from "[http://10.101.68.18/intranet/index.php/GJax\\_gjs:caption](http://10.101.68.18/intranet/index.php/GJax_gjs:caption)"

---

- This page was last modified 17:51, 19 Nov 2005.